

## Specifications Noxion LED Panel Delta Pro V2.0 Highlum 40W 5480lm - 865 Daylight | 62.5x62.5cm - UGR <19 - Dali Dimmable



[View Product](#)

### General Information

|                          |                                                                              |
|--------------------------|------------------------------------------------------------------------------|
| SKU                      | 238066                                                                       |
| EAN                      | 8719157012256                                                                |
| Brand                    | Noxion                                                                       |
| Manufacturer Name        | Noxion LED Panel Delta Pro UGR<19 Highlum V2.0 DALI 40W 5480lm 6500K 625x625 |
| Any Lamp all-in warranty | 6 Years                                                                      |
| Average Lifetime (h)     | 50000                                                                        |
| Series                   | Delta Pro                                                                    |

### Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 40                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 865 Daylight       |
| Colour temperature (Kelvin) | 6500 Daylight      |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 5480               |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 125               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |             |
|----------------|-------------|
| LED panel size | 62.5x62.5cm |
| Length (mm)    | 620         |
| Width (mm)     | 620         |
| Height (mm)    | 32          |

## Why Any-lamp?

## Sensor Information

Type of sensor



Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process