



**Specifications Noxion LED Panel Delta Pro Pronox V2.0 40W 5280lm - 830 Warm White | 60x60cm - UGR <19 - Dali Dimmable**

[View Product](#)

## General Information

|                          |                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------|
| SKU                      | 239503                                                                                    |
| EAN                      | 8719157015486                                                                             |
| Brand                    | Noxion                                                                                    |
| Manufacturer Name        | NEW Noxion LED Panel Delta Pro UGR<19 Highlum V2.0 Xitanium DALI 40W 5280lm 3000K 600x600 |
| Any Lamp all-in warranty | 6 Years                                                                                   |
| Average Lifetime (h)     | 70000                                                                                     |
| Series                   | Delta Pro                                                                                 |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 40                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 5280               |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 120               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |

## Why Any-lamp?

## Sensor Information

Type of sensor



Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process